

Part number:

HYDROMA
HYDRAULICKÉ SYSTÉMY

HIDROMA
SYSTEMS
UKŁADY HYDRAULICZNE

HYDROMA
ГИДРАВЛИЧЕСКИЕ СИСТЕМЫ




VD*-W* CHECK VALVES SERIES 30

p max **400** bar

Q max (see table of performances)

PRESSURE DROPS Δp -Q



OPERATING PRINCIPLE


- VD*-W* valves are check valves with threaded "BSP" ports for mounting in-line on hydraulic lines.
- They allow the flow to pass freely in one direction, blocking it in the opposite direction.
- In rest conditions, the valve poppet is kept closed by a spring. The poppet opens when the pressure in the intake line "A" exceeds the set value of the spring, added to any pressure in the outlet line "B".
- Available in eight sizes for flow rates of up to 850 l/min and with five different cracking pressures.

PERFORMANCES

Valve	BSP port dimension	Maximum flow rate [l/min]	Mass [kg]	Max operating pressure [bar]
VD2-W*	1/4"	25	0,17	400
VD3-W*	3/8"	40	0,26	
VD4-W*	1/2"	75	0,41	
VD5-W*	3/4"	125	0,6	
VD6-W*	1"	200	1,2	320
VD7-W*	1 1/4"	280	1,8	
VD8-W*	1 1/2"	650	3,2	
VD9-W*	2"	850	4,8	

Ambient temperature range	°C	-20 / +60
Fluid temperature range	°C	-20 / +80
Fluid viscosity range	cSt	10 ÷ 400
Fluid contamination degree	cSt	25
Recommended viscosity	acc. to ISO 4406:1999 class 20/18/15	

HYDRAULIC SYMBOL



VD*-W*

SERIES 30

1 - IDENTIFICATION CODE

	V	D		-	W		/	30
--	----------	----------	--	----------	----------	--	----------	-----------

Check valve _____

Nominal dimension _____

2 = 1/4"
3 = 3/8"
4 = 1/2"
5 = 3/4"
6 = 1"
7 = 1 1/4"
8 = 1 1/2"
9 = 2"

Series No.: (The overall and mounting dimensions remain unchanged from 30 to 39)

Cracking pressure: **1** = 0,35 bar
 2 = 2 bar
 T4 = 4 bar
 3 = 6 bar
 4 = 10 bar

BSP threaded ports

2 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4.

Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics.

The fluid must be preserved in its physical and chemical characteristics.

3 - OVERALL AND MOUNTING DIMENSIONS

